

Key to Hub Dimensions			
Prop Model	Flange Type	Hub Thickness	Bushing Dia.
69CK	SAE No.1 Flange	3.190"	.630"
70CM6	SAE No.2 Flange, 3/8" Attaching Bolts	3.437"	.630"
70CM7	SAE No.5 Flange, 7/16" Attaching Bolts	3.437"	.630"
72CC	SAE ARP-502 Flange	3.190"	None
72CK	SAE No.1 Flange	3.190"	.630"
72FM8	SAE No.6 Flange, 1/2" Attaching Bolts	3.437"	.752"
74CK	SAE No.1 Flange	2.750"	.630"
74DC	SAE ARP-502 Flange	3.437"	None
74DM6	SAE No.2 Flange, 3/8" Attaching Bolts	3.437"	.630"
74DM7	SAE No.5 Flange, 7/16" Attaching Bolts	3.437"	.630"
74DR	SAE No.3 Flange	3.437"	.630"
76AM6	SAE No.2 Flange, 3/8" Attaching Bolts	2.750"	.630"
76AK	SAE No.1 Flange	2.750"	.630"
76EC	SAE ARP-502 Flange	3.560"	None
76EM8	SAE No.6 Flange, 1/2" Attaching Bolts	3.560"	.752"